

Production Program Overview



Copper / Alloy *	Thickness	Width ***
Copper		
Cu-ETP / E-Cu58	0.006 mm - 0.500 mm	1 mm - 650 mm **
Cu-HCP / SE-Cu58	0.006 mm - 0.500 mm	1 mm - 650 mm **
Cu-OF / OF-Cu	0.006 mm - 0.500 mm	1 mm - 650 mm **
CuZn0.5	0.006 mm - 0.500 mm	1 mm - 650 mm **
C 155	0.006 mm - 0.100 mm	1 mm - 300 mm **
Brass / Tombak		
CuZn10	0.006 mm - 0.100 mm	1 mm - 650 mm **
CuZn12	0.006 mm - 0.100 mm	1 mm - 650 mm **
CuZn15	0.006 mm - 0.100 mm	1 mm - 650 mm **
CuZn30	0.006 mm - 0.100 mm	1 mm - 650 mm **
CuZn37	0.006 mm - 0.100 mm	1 mm - 650 mm **
Bronze		
CuSn6	0.020 mm - 0.100 mm	1 mm - 320 mm **
Resistance alloys		
CuNi6	0.006 mm - 0.150 mm	1 mm - 320 mm **
CuNi8	0.006 mm - 0.150 mm	1 mm - 320 mm **
CuNi44	0.006 mm - 0.150 mm	1 mm - 625 mm **
Nickel		
Nickel 99.6	0.006 mm - 0.100 mm	1 mm - 625 mm **
Silver		
Silver 99.97%	0.006 mm - 0.100 mm	1 mm - 320 mm **
Silver 99.99%		
Silver 925 (Sterling)		
Nickel-Silver (German Silver / Neusilber)		
CuNi18Zn20	0.020 mm - 0.100 mm	1 mm - 570 mm **
Special materials		
CIC - composite foil (Invar Cu-cladded on both sides, plain or with Cu/Zn-treatment)	0.035 mm - 0.300 mm standard: 0.150 mm	1 mm - 610 mm **
Upgradings		
Surface plated foils	tin-cladding alu-cladding hot-dip tinning silvering nickel-cladding	on one or both sides on one or both sides on one or both sides
Strip finishing	Cu-Treatment acc. to IPC-4562	on one or both sides

* other copper qualities or alloys on request

** depending on thickness

*** most dimensions are also available as sheet, cut to length

Certified Quality Managementsystem acc. to DIN EN ISO 9001 : 2000

Member of IPC and EIPC

Schlenk Metallfolien GmbH & Co. KG
Barnsdorfer Hauptstrasse 5
D-91 154 Roth
Germany

Tel.: +49 - (0)9171 - 808-0
Fax.: +49 - (0)9171 - 808 200
E-mail: foils@schlenk.de
Internet: <http://www.schlenk.de>